

Version No: 1037/551/version4

Date: 3<sup>rd</sup> December 2018Supersedes: 14<sup>TH</sup> January 2015

**PRODUCT NAME:** RESICHEM 551 ER MEMBRANE

**MANUFACTURER:** RESIMAC LTD, UNIT B, PARK BARN ESTATE, STATION ROAD,  
TOPCLIFFE, THIRSK, YO7 3SE, UNITED KINGDOM

**TELEPHONE NUMBER:** +44 (0) 1845 577498

**EMAIL:** info@resimac.co.uk

**EMERGENCY TELEPHONE NUMBER: +44 (0) 1845 577498**

THIS PRODUCT IS A KIT AND SUPPLIED AS A MULTI PART PRODUCT WHICH CONSISTS OF A BASE COMPONENT AND ACTIVATOR COMPONENT. THIS DOCUMENT CONTAINS THE MSDS FOR BOTH BASE AND ACTIVATOR COMPONENTS.

*DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.*

*Date of issue: 14<sup>th</sup> January 2015*

*Document Number 1037/101/version 3:*

Resimac Ltd

Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, North Yorkshire, United Kingdom

Tel: +44 (0) 1845 577498

Email: info@resimac.co.uk

Web: www.resimacsolutions.co.uk

Version No: 1037/551/version4

Date: 3<sup>rd</sup> December 2018

Supersedes: 14<sup>TH</sup> January 2015

## SECTION 1: Identification of Substance/ Preparation and Company

### 1.1 Product identifier

**RESICHEM 551 ER MEMBRANE**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Coatings, paints, thinners and paint removers

### 1.3 Details of the supplier of the safety data sheet

Unit 11, Poplars Industrial Estate, Wetherby Road, Boroughbridge, North Yorkshire, YO51 9HS

Tel: +44 (0) 1423 325073

Email: [info@resimac.co.uk](mailto:info@resimac.co.uk)

### 1.4 Emergency telephone number

+44 (0) 1423 325073 (9am to 5pm)

## SECTION 2: Hazards Identification

### 2.1 Classification of the substance or mixture

Classification in accordance with the Dangerous Preparations Directive 1999/45/EC

Aquatic Chronic 2: H411; FLAM. Liq. 3: H226; Lact: H362

Flammable, Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

May cause harm to breastfed babies. Harmful; may cause lung damage if swallowed

### 2.2 Label elements

Labelling in accordance with the Classification Labelling and Packaging Regulation EC (no) 1272/2008



GHS02 FLAME



GHS09 ENVIRONMENTAL

Pictograms:

Signal Word:

**WARNING**

Hazard Statement:

**H226: Flammable liquid and vapour**

**H362: May cause harm to breast fed children**

**H411: Toxic to aquatic life with long lasting effects**

Resimac Ltd

Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, North Yorkshire, United Kingdom

Tel: +44 (0) 1845 577498

Email: [info@resimac.co.uk](mailto:info@resimac.co.uk)

Web: [www.resimacsolutions.co.uk](http://www.resimacsolutions.co.uk)

Version No: 1037/551/version4

Date: 3<sup>rd</sup> December 2018Supersedes: 14<sup>TH</sup> January 2015**Precautionary statements:****P243: Take precautionary measures against static charge****P264: Wash hands with soap thoroughly after handling****P280: Wear protective gloves/protective clothing/eye protection/face protection .****P303 + P361 + P353: IF ON SKIN: Rinse cautiously with water for several minutes.****Remove immediately all contaminated clothing.****P308+313: IF exposed or concerned: Get medical advice/ attention****SECTION 3: Composition/ Information on Ingredients****3.1 Substances**

Not applicable, product is a mixture.

**3.2 Mixtures**

Contains the following hazardous components above thresholds of concern:

Hazardous Components	Cas Number	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No 1272/2008
Hydrocarbons and aromatics	918-688-5	10-30%	Xi: R37; N: R51/53; Xn: R65; R66; R67; R10	Flam Liq.3: H226; Aquatic Chronic 2; H411; Asp. Tox 1; H304; STOT SE 3: H335
Alkanes	85535-85-9	1-10%	Lact: H362; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	R64; R66; N: R50/R53
Quarternary Ammonium Compounds	61789-73-9	<1%	C: R34; N: R50/R53	Aquatic Chronic 1: H410; Skin Corr.1C: H314
Cumene	98-82-8	<1%	R10; Xi: R37; N: R51/53; Xn: R65	Flam Liq.3: H226; Asp.Tox 1: H304; STOT SE 3: H335; Aquatic Chronic 2: H411
2-Methoxypropyl Acetate	70657-70-4	<1%	T: T61; R10; Xi: R37	Flam Liq.3: H226; Repr.1B: H360D; STOT SE 3: H335

See section 16 for full description of R phrases and H statements.

**SECTION 4: First Aid Measures****4.1 Description of first aid measures***Summon immediate medical assistance after contact with skin, eyes, inhalation or ingestion***Eye:** Flush eyes with plenty of running water for 15 minutes, whilst gently holding the eyelids open. If signs/symptoms persist seek medical attention.**Skin:** Remove product and contaminated clothing and wash area with water, seek medical advice.

Resimac Ltd

Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, North Yorkshire, United Kingdom

Tel: +44 (0) 1845 577498

Email: [info@resimac.co.uk](mailto:info@resimac.co.uk)Web: [www.resimacsolutions.co.uk](http://www.resimacsolutions.co.uk)

Version No: 1037/551/version4

Date: 3<sup>rd</sup> December 2018

Supersedes: 14<sup>TH</sup> January 2015

**Ingestion:** Drink plenty of water, DO NOT INDUCE VOMITING. If you feel unwell get medical attention

**Inhalation:** Irritation may cause coughing, tightness of the chest and irritation of the respiratory system. Remove patient to fresh air. Seek medical advice.

#### 4.2 Most important symptoms and effects, both acute and delayed

*Eye Contact:* Sign/ Symptoms Contact with eyes during product use may cause irritation.

*Skin Contact:* Sign/ Symptoms Contact with the skin during product use may cause skin irritation

*Inhalation:* Sign/ Symptoms No data available

*Ingestion:* Signs/ Symptoms No data available

#### 4.3 Indication of any immediate medical attention and special treatments needed

Symptomatic treatment as required

### SECTION 5: Fire Fighting Measures

#### 5.1 Extinguishing media

Carbon dioxide

#### 5.2 Special hazards arising from the substance or mixture

Burning produces toxic fumes

#### 5.3 Advice for fire fighters

Wear Self-contained breathing apparatus, rubber boots, gloves and body suit

### SECTION 6: Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all unnecessary personnel from the area. Ventilate the area if possible. Wear suitable protective clothing including chemical resistant gloves and coveralls. If vapour concentrations are high, respiratory protective equipment may be required. See section 8 for more information.

#### 6.2 Environmental precautions

Prevent entry into sewers and watercourses. If product enters sewers or watercourses, inform the appropriate environmental authorities.

#### 6.3 Methods and materials for containment and clearing up

Scrape up and transfer into a suitable container. Wash area with water.

#### 6.4 References to other sections

Refer to section 5, 8 and 13 for protective Measures and Disposal.

Resimac Ltd

Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, North Yorkshire, United Kingdom

Tel: +44 (0) 1845 577498

Email: [info@resimac.co.uk](mailto:info@resimac.co.uk)

Web: [www.resimacsolutions.co.uk](http://www.resimacsolutions.co.uk)

Version No: 1037/551/version4

Date: 3<sup>rd</sup> December 2018

Supersedes: 14<sup>TH</sup> January 2015

## **SECTION 7: Handling and Storage**

### **7.1 Precautions for safe handling**

Avoid contact with skin, eyes and clothing. Handle in well ventilated area. Wash hands after contact.  
Keep away from sources of ignition – NO SMOKING

### **7.2 Conditions for safe storage, including any incompatibilities**

Keep container tightly closed in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

### **7.3 Specific end uses(s)**

Coatings and paints, thinners, paint removers.

## **SECTION 8: Exposure Controls/ Personal Protection**

### **8.1 Control parameters**

No data available

### **8.2 Exposure controls**

**Engineering controls** Adequate ventilation should be provided.

**Respiratory:** Self-contained breathing apparatus must be available in case of emergency

**Hand Protection** Impermeable gloves

**Skin Protection:** Avoid Skin Contact; use disposable coveralls

**Eye Protection:** Avoid Eye Contact; use safety goggles meeting the requirements of BS EN166 3, when handling this product

### **Environmental Exposure controls**

Take suitable measures to prevent entry into drains, sewers and watercourses.

## **SECTION 9: Physical/ Chemical Properties**

### **9.1 Information on basic physical and chemical properties**

<b>Appearance:</b>	Viscous liquid
<b>Odour:</b>	Characteristic Odour
<b>Density:</b>	1.35g/ml
<b>Boiling Point/ range:</b>	145-181°C
<b>Flash Point:</b>	35°C
<b>VOC g/l:</b>	450

### **9.2 Other information**

None.

Resimac Ltd

Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, North Yorkshire, United Kingdom

Tel: +44 (0) 1845 577498

Email: [info@resimac.co.uk](mailto:info@resimac.co.uk)

Web: [www.resimacsolutions.co.uk](http://www.resimacsolutions.co.uk)

Version No: 1037/551/version4

Date: 3<sup>rd</sup> December 2018

Supersedes: 14<sup>TH</sup> January 2015

## SECTION 10: Stability And Reactivity

### 10.1 Reactivity

Not considered to be a reactive product

### 10.2 Chemical stability

Stable

### 10.3 Possibility of hazardous reactions

Hazardous Polymerisation is not likely to occur.

### 10.4 Conditions to avoid

Excessive heat. Direct sunlight. Sources of ignition.

### 10.5 Incompatible materials

Oxidising agents – cleaning solutions. Acids.

### 10.6 Hazardous decomposition products

In combustion emits toxic fumes

## SECTION 11: Toxicological Information

### 11.1 Information on toxicological effects

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

HYDROCARBONS C9 AROMATICS	DERMAL DL50 >3160 mg/kg ORAL RAT LD50 3492 mg/kg
CUMENE	ORAL MUS LD50 12750 mg/kg ORAL RAT LD50 1400 mg/kg

## SECTION 12: Ecological Information

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

Resimac Ltd

Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, North Yorkshire, United Kingdom

Tel: +44 (0) 1845 577498

Email: [info@resimac.co.uk](mailto:info@resimac.co.uk)

Web: [www.resimacsolutions.co.uk](http://www.resimacsolutions.co.uk)

Version No: 1037/551/version4

Date: 3<sup>rd</sup> December 2018

Supersedes: 14<sup>TH</sup> January 2015

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

Readily absorbed into soil

**12.5 Results of PBT and vPvB assessment**

None of the components are known to be PBT or vPvB.

**12.6 Other adverse effects**

Toxic to aquatic organisms. Adverse effects on water treatment plants

**SECTION 13: Disposal Considerations**
**13.1 Waste treatment methods**

In uncured state, dispose as chemical waste in accordance with local regulations. Waste from this product may present long term environmental hazards. Thus landfill sites must be considered less acceptable than incineration.

In cured state when mixed correctly with the base component, dispose as solid waste

Empty containers should be disposed of as chemical waste.

**SECTION 14: Transport Information**

**General:** Transport and labelling requirements will alter depending on the size of the packaging. Please refer to local transport regulations.

	ADR	IMDG	ICAO
14.1 UN Number	UN1263	UN1263	UN1263
14.2 UN Proper shipping name	Paint	Paint	Paint
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	Marine Pollutant	Marine Pollutant	Marine Pollutant
14.6 Special precautions for user			
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable	Not applicable	Not applicable

Resimac Ltd

Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, North Yorkshire, United Kingdom

Tel: +44 (0) 1845 577498

Email: [info@resimac.co.uk](mailto:info@resimac.co.uk)

Web: [www.resimacsolutions.co.uk](http://www.resimacsolutions.co.uk)

Version No: 1037/551/version4

Date: 3<sup>rd</sup> December 2018

Supersedes: 14<sup>TH</sup> January 2015

## **SECTION 15: Regulatory Information**

### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

All components are listed as existing substances in Europe

All components are listed, or are exempt from listing on the TCSA Inventory

### **15.2 Chemical Safety Assessment**

A Chemical Safety Assessment has not been carried out for this product.

## **SECTION 16: Other Information**

### **Revision information:**

Reformatted in accordance with Regulation 453/2010 and Regulation 1272/2008.

### **List of Abbreviations used in this SDS:**

CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging Regulation (EC) no 1272/2008
DSD	Dangerous Substances Directive 67/548/EEC
DPD	Dangerous Preparations Directive 1999/45/EC
EC	European Community/Commission
PBT	Persistent, Bioaccumulative and Toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) no 1907/2006
vPvB	very Persistent, very Bioaccumulative

### **References:**

ECHA Classification and Labelling inventory

ECHA database of disseminated registration dossiers

Supplier's Safety Data Sheets

### **Method used for classification of mixtures:**

Ingredient based approaches

### **P Phrases and H Statements used in Section 3**

H226: Flammable liquid and vapour

H304: May be fatal if swallowed and enters airways

H314: Causes severe burns and eye damage

H335: May cause respiratory irritation

H336: May cause drowsiness or dizziness

H360D: May damage the unborn child

H362: May cause harm to breast fed children

H411: Toxic to aquatic life with long lasting effects

### **Resimac Ltd**

Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, North Yorkshire, United Kingdom

Tel: +44 (0) 1845 577498

Email: [info@resimac.co.uk](mailto:info@resimac.co.uk)

Web: [www.resimacsolutions.co.uk](http://www.resimacsolutions.co.uk)



Version No: 1037/551/version4

Date: 3<sup>rd</sup> December 2018Supersedes: 14<sup>TH</sup> January 2015

P202: Do not handle until all safety precautions have been read and understood.

P280: Wear protective gloves/protective clothing/eye protection/face protection .

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a doctor

**Training requirements for workers**

No special training requirements.

**Resimac Ltd**

Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, North Yorkshire, United Kingdom

Tel: +44 (0) 1845 577498

Email: [info@resimac.co.uk](mailto:info@resimac.co.uk)

Web: [www.resimacsolutions.co.uk](http://www.resimacsolutions.co.uk)