

RESICHEM 551 ER Membrane

Resichem 551 ER Membrane is a single pack solvent based acrylic water proof coating. The product is supplied ready to use and is ideal for waterproofing flat roofs, pitched roofs, gutters, felt and fibreglass. The product is highly fibrous and has excellent crack or gap bridging qualities and is not adversely affected by rainwater 30 minutes after application.

Typical applications

Flat and pitched roofs, weathered asphalt and bituminous surfaces, gutters, brickwork, fibreglass, felt and metal surfaces.

Surface Preparation

Clear all areas of moss, lichen and debris by brushing or power washing and remove surface water and any contamination such as oil or grease and allow to dry as much as possible.

Most roofing surfaces and substrates will not require any primer.

Application temperature should be between 5°C-25°C (40°F-77°F).

1. Metallic substrates

This product can be applied to Ferrous (New), weathered and previously painted and galvanised iron and steel, Non Ferrous metals such as Aluminium sheeting, aluminium alloy box gutter and previously painted non-Ferrous metals.

2. Porous/ friable surfaces

Concrete and Asbestos cladding, sheeting and guttering should be primed with Resichem 505 Damp Seal prior to overcoating with Resichem 551 ER Membrane.

3. Non porous surfaces

Slate, polished bricks should be power washed, abraded and completely dry, free from contamination to achieve adhesion with Resichem 551 ER Membrane.

4. Bitumen surfaces

Discolouration may occur over new asphalt, tar or bitumen surfaces, therefore an extra coat of Resichem 551 ER Membrane may be required for decorative purposes only.

5. Previously painted or coated surfaces

It is good practice to inspect and carry out adhesion tests on any existing coating or substrate prior to the application of Resichem 551 ER Membrane.

6. Splits, cracks, joints and seals

Pay particular attention to any cracks, joints, splits and seals and ensure that the area has been cleaned out by scraping or brushing any debris away from the repair area.

PLEASE NOTE:

Resichem 551 ER Membrane is not recommended for the treatment of tanking, fishponds or internal use. Air conditioning vents should be sealed for 24 hours during and after application of this product.

As an appropriate cleaner use MEK.

Mixing and Application

Resimac Ltd, Unit B, Park Barn Estate, Station Road, Topcliffe, Thirsk, YO7 3SE, United Kingdom

Tel: +44 1845 577498 Email: info@resimac.co.uk Web: www.resimacsolutions.com

