

**SAFETY DATA SHEET**  
RESICHEM 593 EPOXY AS BASE COMPONENT

Page: 1  
Compilation date: 21/11/2018  
Revision No: 2

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** RESICHEM 593 EPOXY AS BASE COMPONENT

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Resimac Limited  
Unit B, Park Barn Estate  
Station Road  
Topcliffe, Thirsk  
North Yorkshire  
YO7 3SE  
United Kingdom  
**Tel:** +44 (0) 1845 577498  
**Email:** [info@resimac.co.uk](mailto:info@resimac.co.uk)

**1.4. Emergency telephone number**

**Emergency tel:** +44 (0) 1845 577498

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CHIP:** Xi: R36/38; Sens.: R43; N: R51/53

**Classification under CLP:** Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -: EUH205

**Most important adverse effects:** Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** EUH205: Contains epoxy constituents. May produce an allergic reaction.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H411: Toxic to aquatic life with long lasting effects.

**Signal words:** Warning

**Hazard pictograms:** GHS07: Exclamation mark  
GHS09: Environmental

[cont...]

# SAFETY DATA SHEET

RESICHEM 593 EPOXY AS BASE COMPONENT

Page: 2



**Precautionary statements:** P102: Keep out of reach of children.  
P273: Avoid release to the environment.  
P264: Wash skin thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+313: If skin irritation or rash occurs: Get medical advice/attention.  
P501: Dispose of contents/container to hazardous or special waste collection point.

## Label elements under CHIP:

**Hazard symbols:** Irritant.  
Dangerous for the environment.



**Risk phrases:** R36/38: Irritating to eyes and skin.  
R43: May cause sensitisation by skin contact.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S2: Keep out of the reach of children.  
S24: Avoid contact with skin.  
S29: Do not empty into drains.  
S37: Wear suitable gloves.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

## 2.3. Other hazards

## Section 3: Composition/information on ingredients

**PBT:** This product is not identified as a PBT/vPvB substance.

## 3.2. Mixtures

### Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	CHIP Classification	CLP Classification	Percent
--------	-----	---------------------	--------------------	---------

[cont...]

**SAFETY DATA SHEET**  
RESICHEM 590 EPOXY FC BASE COMPONENT

Page: 3

500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
-----------	------------	-----------------------------------	--	--------

**BISPHENOL F TYPE EPOXY RESIN**

500-108-2	28064-14-4	Xi: R36/38; N: R51/53; Sens.: R43	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
-----------	------------	-----------------------------------	--	--------

**OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES**

271-846-8	68609-97-2	Xi: R38; Sens.: R43	Skin Irrit. 2: H315; Skin Sens. 1: H317	1-10%
-----------	------------	---------------------	---	-------

**Section 4: First aid measures**

**4.1. Description of first aid measures**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Not applicable.

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Not applicable.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Alcohol or polymer foam. Dry chemical powder. Carbon dioxide.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus.

**Section 6: Accidental release measures**

[cont...]

# SAFETY DATA SHEET

RESICHEM 590 EPOXY FC BASE COMPONENT

Page: 4

## 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

## 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

## 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

## 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Avoid incompatible materials and conditions - see section 10 of SDS.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

### 8.2. Exposure controls

**DNEL / PNEC:** No data available.

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses.

**Skin protection:** Impermeable protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

[cont...]

**SAFETY DATA SHEET**  
RESICHEM 590 EPOXY FC BASE COMPONENT

Page: 5

**Colour:** Various  
**Odour:** Barely perceptible odour  
**Evaporation rate:** Negligible  
**Oxidising:** Non-oxidising (by EC criteria)  
**Solubility in water:** Insoluble  
**Viscosity:** Non-viscous  
**Boiling point/range°C:** >200  
**Flash point°C:** >150  
**Relative density:** 1.75g/cc

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

**10.4. Conditions to avoid**

**Conditions to avoid:** Direct sunlight. Flames.

**10.5. Incompatible materials**

**Materials to avoid:** Strong acids. Strong oxidising agents. Amines. Alkalis.

**10.6. Hazardous decomposition products**

**Section 11: Toxicological information**

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

**11.1. Information on toxicological effects**

**Toxicity values:**

Route	Species	Test	Value	Units
ORAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

[cont...]

**SAFETY DATA SHEET**  
RESICHEM 590 EPOXY FC BASE COMPONENT

Page: 6

**Hazardous ingredients:**

**BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}**

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

**OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES**

ORL	RAT	LD50	17100	mg/kg
-----	-----	------	-------	-------

**Relevant effects for mixture:**

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Not applicable.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:**

Species	Test	Value	Units
FISH	96H LC50	2	mg/l

**12.2. Persistence and degradability**

**Persistence and degradability:** Not biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** Bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Insoluble in water.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

[cont...]

**SAFETY DATA SHEET**  
RESICHEM 590 EPOXY FC BASE COMPONENT

Page: 7

**12.6. Other adverse effects**

**Other adverse effects:** Toxic to aquatic organisms.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company. Mixed material, once fully cured, can be disposed as solid waste.

**Waste code number:** 08 04 09

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN3082

**14.2. UN proper shipping name**

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT})

**14.3. Transport hazard class(es)**

**Transport class:** 9

**14.4. Packing group**

**14.5. Environmental hazards**

**Packing group:** III

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

**14.6. Special precautions for user**

**Tunnel code:** E

**Transport category:** 3

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

[cont...]

**SAFETY DATA SHEET**  
RESICHEM 590 EPOXY FC BASE COMPONENT

Page: 8

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.